appliansys

CACHEBOX050/100 series

PERFORMANCE CACHING SENSIBLE PRICES

OVERVIEW

CACHEBOX050 and CACHEBOX100 series are light duty web caching appliances designed for schools, SMEs, branch offices and small ISPs. They combine feature rich caching software with the security, reliability and ease-of-use of the appliance format.

CACHEBOX050 is a small form factor device, about the size of a standard laptop. CACHEBOX110 offers the same performance levels in a 1U rack-mountable version. CACHEBOX130 offers higher perfomance and high availability with Fail-to-Wire and KVM functionality. You can use these alone or with larger CACHEBOX models deployed further upstream.

If you plan to deploy more than 5 or 6 appliances, either clustered in a datacentre or distributed across many locations, you can simplify their configuration, management and recovery with the **CACHE**BOX Central Management Console (CMC). For more information see the **CACHE**BOX**cmc** fact sheet.



FEATURES & BENEFITS

Save bandwidth, save money

- Fully featured caching software support for HTTP
- Video caching (YouTube, Metacafe, Vimeo, Dailymotion, Veoh etc)
- Software update caching (MS Windows, Apple, Avast, Kaspersky etc)
- Off-peak pre-caching of content

Flexible deployment

- Multiple transparent and explicit deployment modes
- Fail-to-Wire resiliency
- Clustering, load balancing and hierarchies
- WCCP Support (v.2, GRE and Layer 2)
- IP spoofing
- Firewall with NAT forwarding for networking flexibility

* Note: Fail-to-Wire available on CACHEBOX130 only, offering two additional Fail-toWire NICs

• iKVM remote access technology



Easier to manage

- Intuitive, secure web admin interface
- Setup and caching assistants
- On-box graphical reporting / scheduled reporting to monitor caching and network performance
- Automated on-box / off-box backups
- Automated alerting
- Multi-lingual interface
- Control and administer multiple users
- Validated and automated data entry
- Operating system runs from read-only
 Industrial CFast
- SNMP support
- Custom ACLs support
- Logging

Browse safely and log activity

- Secure HTTPS and SSH management interface
- MS Active Directory integration via NTLM
 and Kerberos authentication

RANGE

	CACHEBOX050	X050 CACHEBOX100 Series	
		110	130
Usage	Small branch office/school	Small office/school/ISP	Premium Light Duty
*Performance	400 HTTP RPS / 40Mbps		500 HTTP RPS / 60Mbps
Disk Drives	1 x HDD Object Storage		
High Availability	N/A	λ.	KVM & Fail-to-Wire
Ethernet (NICs)	2 x 10/100/1000		
Flash Storage	1 x OS and data	1 x OS	& 1 x data
OS	Linux		
Form Factor	Small Form Factor	19" 1U Rack-mountable	
Dimensions	305mm x 54mm x 279mm	482.6mm x 44.45mm x 254mm	
Weight (Max)	4.5KG	5KG	
Power	100-240V AC		
Max Power	80W		220W
Temperature	5°C to 35°C (41°F to 95°F)		
Humidity	Less than 85% relative humidity, non-condensing		

* Peak performance achieved under test conditions. Real life performance limits vary, depending on network and traffic characteristics